

CENTURION ULTRA

Featuring 1/1.9" Sony HD Technology for incredible colour or mono images at night





Product Data Sheet



1/1.9" SENSOR FOR **ULTRA LOW LIGHT** PERFORMANCE

High Speed High Definition Ruggedised Pan, Tilt and Zoom Camera

UK Manufacture

Designed and Manufactured in the UK.

Paint Colour Options

Any colour, any quantity.

IP Multi Stream Codec

2 Codec streams up to 1080p (25fps/30fps) 2MP resolution.

Optical Zoom

Massive 32x optical zoom with Auto Focus

Protocols

ONVIF 'S' compliant or 360SDK, see our web site for the many compatible VMS systems.

Sirius Illumination Intelligent Lighting control

Sirius illumination automatically adjusts the lighting intensity to ensure the highest quality images under variable lighting conditions.

Sirius Illumination

Optional IR only or IR and White Light.

IP67 Certification

IP67 certified for the harshest environments.

360 Ultra Low Light cameras

360 Ultra low light cameras with mono video images as low as 0.0002 lux (no illumination)

Privacy Zones

24 privacy zones are available with simple joystick positioning and sizing.

Marine Paint

10 year marine paint option.

Warranty


3 year warranty






Centurion ULTRA


Centurion with no lamps Weight: 7kg



Centurion with lamp Weight: 7.5kg



Hinged Mount Adapter with lamp Weight: 9kg



| PRODUCT SPECIFICATION | 23x ULTRA | | | 32X ULTRA | |
|------------------------------|--|----------------|-------------------|--------------|--|
| Colour/Mono | Yes | | Yes | | |
| Imager (CMOS) | 1/1.9" Sony Exmor | | 1/1.9" Sony Exmor | | |
| Zoom - Optical + Digital | 23x, 12x | | 32x, 12x | | |
| Zoom - Total | 276× | 384x | | | |
| Pixels (Megapixels) | Approx 2.38 | | Approx 2.38 | | |
| Horizontal view angle | 60°(W)-3.2°(T) | 60°(W)-2.2°(T) | | | |
| Lens Size | 6-192mm | | | | |
| Min Sensitivity - colour | 0.002 Lux 0.002 Lux | | | | |
| Min Sensitivity - mono Int | 0.0002 Lux | 0.0002 Lux | | | |
| Signal Noise Ratio | >50dB | >50dB | | | |
| Picture Flip | Yes | | Yes | | |
| Picture Freeze | Yes | | Yes | | |
| PRODUCT FEATURES | ALL Centurion units have the following functions | | | | |
| Focus/Iris | Auto/Manual | | | | |
| Presets | 101 | | | | |
| Tours | 4 (max 90 presets per tour) | | | | |
| Learned Patrols | 4 mimic tours - up to 10 minutes duration each | | | | |
| Privacy Zones | Up to 24 | | | | |
| Variable pan speed/coverage | 0.1 - 120°/sec, 360° continuous rotation, absolute positioning | | | | |
| Variable tilt speed/coverage | 0.1 - 120º/sec, 160º, absolute positioning | | | | |
| Auto Homing | Goes to preset, tour or mimic tour after prescribed time | | | | |
| Col/Mono Changeover | 4 levels - 3 fixed, 1 custom/user defined | | | | |
| Operating temperature | -30°C to +60°C | | | | |
| Power | 24vac/30vdc | | | | |
| Mounting options | Wall, Corner, Pole and Soffit | | | | |
| Certification | CE approval; Ingress IP67 | | | | |
| SIRIUS ILLUMINATION | IR or IR & WHITE LIGHT (Nominal) | | | | |
| IR80 | IR 80 metres | | | | |
| IR110WL | IR 110 metres, WL 100 metres | | | | |
| WEIGHTS | | | | | |
| Centurion (No lamps) | 7kg | | | | |
| Centurion (With lamps) | 7.5kg | | | | |
| CODEC | 25fps | ASPECT | | 30fps | |
| HD1080p | 1920x1080 | 16:9 | | 1920×1080 | |
| HD720p | 1280x720 | 16:9 | | 1280×720 | |
| D1 | 720x576 | 4:3 | | 720×480 | |
| VGA | 640x480 | 4:3 | | 640x480 | |
| QVGA | 432x240 | 16:9 | | 432x240 | |
| Distribution | Multi Codec 2 streams | | | | |
| Image Compression | H.264, MPEG4, MJPEG | | | | |
| Protocols | ONVIF (S), TCP/IP, HTTPS, RTP, RTSP, 360SDK, QoS | | | | |
| Compression levels | CBR, VBR CVBR | | | | |
| Standard Paint Options | RAL | | | | |
| Black | 9005 | | | | |
| White | 9003 | | | | |

All trademarks are used courtesy of registered owners. CENTURION ULTRA is a registered trademark of 360 Vision Technology Ltd. The manufacturer reserves the right to change specifications without notice.



360 Vision Technology Ltd
Unit 7 Seymour Court Manor Park Runcorn Cheshire WA7 1SY UK
Tel:+44 (0)870 903 3601 Fax:+44 (0)870 903 3602
info@360visiontechnology.com info@360visiontechnology.com www.360visiontechnology.com

