



Product Brochure

CENTURION HYBRID

Analogue 4:3
[HD Quality]

Full HD 1080p



From this



To this



Centurion Hybrid
Analogue & HD
in ONE
PTZ Camera

No additional equipment required.



CENTURION HYBRID



FULL 1080P HIGH DEFINITION VIDEO

Introducing the Patent Pending Centurion Hybrid Dual output HD AND Analogue PTZ Camera Range.



Future Proofing CCTV Surveillance Systems

360 Vision are proud to launch the World's first Dual Output Analogue and High Definition Range of PTZ cameras.

Offering true 4:3 High Resolution Analogue video (delivered via conventional coaxial cable) AND 16:9 High Definition IP Video, Centurion Hybrid provides a "HD Ready" experience for all existing analogue systems and delivering an extremely cost effective return on investment for the future.

Using Centurion Hybrid, the customer gains the ability to install what appears to be a conventional analogue camera, with a familiar video over coax cable and RS485 Telemetry data over twisted pair (or coax!).

Within the Centurion Hybrid sits a Full HD 1080p 30x autofocus camera that provides near HD video over conventional analogue coax cable when in Analogue mode.

Existing analogue control systems, such as video matrices and Digital Video Recorders (DVRs) are still able to take analogue control and video from Centurion Hybrid - even using 3rd party protocols such as Pelco, VCL, Forward Vision, Ultrak and more.

Centurion Hybrid can also offer conventional ethernet connectivity out via CAT6 ethernet cable to offer streaming via IP protocols. Including ONVIF and 360's own proprietary SDK - thus allowing current or future connection to ALL of the industry's leading VMS solutions such as IndigoVision, Exacq, Milestone, Genetec, Avigilon and ANY ONVIF approved VMS.

"Quite literally, install the HD Ready cameras today over your existing system and come the time you are ready to upgrade to IP, enjoy HD images instantly and WITHOUT changing your cameras again!"





Product Brochure

CENTURION HYBRID



High Speed High Definition ANALOGUE and 1080p HD output ruggedised Pan, Tilt and Zoom Camera

UK Manufacture

Designed and Manufactured in the UK.

Paint Colour Options

Any colour, any quantity.

IP Protocols

ONVIF 'S' compliant or 360SDK, see our web site for the many compatible VMS systems.

Analogue Protocols

360 (RS485/Coax), Pelco (RS485/Coax), VCL (RS485/Coax), Forward Vision and Ultrak (RS485)

Sirius Illumination Intelligent Lighting control

Sirius illumination automatically adjusts the lighting intensity to ensure the highest quality images under variable lighting conditions.

Sirius Illumination

Full range of Dual IR & White Light options. Up to 110 metres of IR lighting and up to 110 metres of white light giving 'COLOUR VIDEO at NIGHT'. Sirius illumination combines narrow, medium and wide angle lenses to give a wide range of light spread (from 9° to 45°). Choice of standard IR 850nm or covert 940nm available.

IP67 Certification

IP67 certified for the harshest environments.

360 Enhanced Low Light cameras

360 Enhanced low light cameras with mono video images as low as 0.0008 lux (no illumination)

Privacy Zones

24 privacy zones are available with simple joystick positioning and sizing.

Centurion Hybrid: Patent Pending

Option giving ANALOGUE and 1080p HD output/control, for system migration to full HD.

Maritime Paint

10 year maritime paint option.

Warranty


3 year warranty



Centurion HYBRID

Hinged Mount Adapter with lamp



Weight: 9kg



Centurion Bracketry



Wall Bracket
Weight: 1.2kg

Corner Bracket
Weight: 2.2kg



Pole Mount Adapter (PMA)
Weight: 1 kg

Pole Mount Bracket (PMB)
Weight: 2.5kg



PRODUCT SPECIFICATION	30x HD	20x HD	30x HD ENHANCED LOW LIGHT
Colour/Mono	Yes	Yes	Yes
Imager (CMOS)	1/2.8-type Exmor	1/2.8-type Exmor R	1/2.8-type Exmor R
Zoom - Optical + Digital	30x, 12x	20x, 12x	30x, 12x
Zoom - Total	360x	240x	360x
Pixels	Approx 2.38 Megapixels	Approx 2.14 Megapixels	Approx 2.13 Megapixels
Horizontal view angle	2.3°(T) - 63.7°(W)	3.3°(T) - 59.5°(W)	2.3°(T) - 63.7°(W)
Lens Size	4.3 - 129mm	4.7 - 94mm	4.3 - 129mm
Min Sensitivity - colour	0.1 Lux	0.1 Lux	0.0013 Lux
Min Sensitivity - mono Int	0.013 Lux	0.008 Lux	0.0008 Lux
Signal Noise Ratio	>50dB	>50dB	>50dB
Picture Flip	Yes	Yes	Yes
Picture Freeze	Yes	Yes	Yes
PRODUCT FEATURES	ALL Centurion units have the following functions		
Focus/Iris	Auto/Manual		
Presets	101		
Tours	4 (max 90 presets per tour)		
Learned Patrols	4 mimic tours - up to 10 minutes duration each		
Privacy Zones	Up to 24		
Variable pan speed/coverage	0.1 - 120°/sec, 360° continuous rotation, absolute positioning		
Variable tilt speed/coverage	0.1 - 120°/sec, 160°, absolute positioning		
Auto Homing	Goes to preset, tour or mimic tour after prescribed time		
Col/Mono Changeover	4 levels - 3 fixed, 1 custom/user defined		
Operating temperature	-30°C to +60°C		
Power	24vac/30vdc		
Mounting options	Wall, Corner, Pole and Soffit		
Certification	IP67		
SIRIUS ILLUMINATION	IR & WHITE LIGHT (Nominal)		
IR80	IR 80 metres		
IR110WL	IR 110 metres, WL 110 metres		
WEIGHTS			
Centurion (HMA No lamps)	8.5kg		
Centurion (HMA with lamp)	9kg		
CODEC	25fps	ASPECT	30fps
HD1080p	1920x1080	16:9	1920x1080
HD720p	1280x720	16:9	1280x720
D1	720x576	4:3	720x480
VGA	640x480	4:3	640x480
QVGA	432x240	16:9	432x240
Distribution	Multi Codec 2 streams		
Image Compression	H.264, MPEG4, MJPEG		
Protocols	ONVIF (S), TCP/IP, HTTP, RTP, RTSP, 360SDK		
Compression levels	CBR, VBR CVBR		
Standard Paint Options	RAL		
Black	9005		
White	9003		

All trademarks are used courtesy of registered owners. Centurion HYBRID is a registered trademark of 360 Vision Technology Ltd. The manufacturer reserves the right to change specifications without notice.



360 Vision Technology Ltd

Unit 7 Seymour Court Manor Park Runcorn Cheshire WA7 1SY UK

Tel: +44 (0)870 903 3601 Fax: +44 (0)870 903 3602

info@360visiontechnology.com

www.360visiontechnology.com





360VISION
TECHNOLOGY