



Product Brochure

VISIONMATRIX & VISIONKEYBOARD



VisionMatrix: Intelligent telemetry control matrix



VisionKeyboard

Cost effective solution

The 360 Vision Technology Ltd Vision Matrix and Vision Keyboard combine to give a powerful and cost effective CCTV matrix solution with total compatibility to the VisionDome range.

Up to 256 camera inputs

The VisionMatrix is available with 8, 16, 32, 48, 64, 128, 192 and 256 camera inputs – each with full telemetry control.

Up to 12 monitor outputs

The VisionMatrix is available with 2, 4 or 12 monitor outputs.

Up to 7 control keyboard

Up to 7 VisionKeyboards can control a VisionMatrix BM with RS232 input for PC/DVR control.

"In Coax" and "TP" telemetry

Telemetry control is selected on each video channel giving a mix of "in-coax" and "twisted pair/RS485" in the same system.

Integration – DVR & Transmission

The VisionMatrix provides seamless control of 360 VisionDomes by third party DVR and IP transmission products.

Comprehensive alarm handling

Up to 144 alarms, each capable of instigating multiple camera actions, programmed via matrix menu screen.

360 High Speed PTZ cameras

All 360 High Speed PTZ camera features can be accessed from the VisionMatrix to enable first line, remote maintenance.

On screen menu

A simple on screen menu system enables easy and intuitive system set up.

Variable speed PTZ

Dome speeds of between 0.1°/s to 400°/s (pan) are controlled with the VisionKeyboard's 3 axis joystick – speeds adjust in proportion to the zoom position.

Shop Monitor/Podium

VisionDomes used for surveillance purposes can be prevented from appearing on shop monitor/podium positions.



VisionMatrix Series



VisionMatrix BM Series

VISIONMATRIX FEATURES	VISIONMATRIX 8x2, 16x2	VISIONMATRIX [STACK] 32x2, 48x2, 64x2	VISIONMATRIX (BM) 32X4, 64X4, 64X12	VISION MATRIX (BM CASCADE-ABLE) 128x12, 192x12, 256x12
Camera Inputs	8, 16	32, 48, 64	32, 64	128, 192, 256
Individual Input Termination	Yes			
Monitor Outputs	2		4, 12	12
Control Ports	2 x RS485 1 x RS232	1 x RS485 1 x RS232	5 x RS485 2 x RS232	3 x RS485 1 x RS232
Dome/Alarm ports	1 x RS485			
Alarm inputs on Matrix	16		None	
Total Alarms (Matrix & Alarmcards)	144		128	
Relay Output	1		None	
RS485/TP Control	Yes			
Co-ax Control	Yes (up-to 4 monitors)			No (12 monitors)
Line-Lock	Yes	No	Yes	
Keyboard Lock/Unlock	Yes			
Shop Monitor	Yes		No	
Podium	No		Yes	
Auto-Sequence	Yes			
OSD Menu Operation	Yes			
Op/Con/Eng access levels	Yes			
Camera, Preset & Alarm titling	Yes			
Buzzer Off/On	Yes			
Proportional Speed Control	Yes			
Remote gain/Lift	Yes			
Protocol	360 Vision Technology			
Weight	2.9Kg	8.7, 11.6, 14.5Kg	8.5kg	12Kg (128/12)
Power Supply (included)	12Vdc		24Vdc	
Operating Temp/Humidity	5°C to 40°C/0% to 90%			
Approval Certification	CE Approval			
VISIONKEYBOARD	MATRIX KEYBOARDS			BM MATRIX KEYBOARDS
Model	VKMD485	VKAVXM485	VKAVXM232	VKAVXBM485
LCD	No	Yes		
RS485 (additional ports are used for 360 DVR control)	1	1 x Matrix 1 x DVR	1 x DVR	1 x Matrix 1 x DVR
RS232 (additional ports are used for 360 DVR control)	0	1 x DVR	1 x Matrix 1 x DVR	1 x DVR
DVR Control	No	Yes		
DVR Models	N/A	Avalon T, H		
Power Supply (included)	12Vdc			
Weight/Shipping Weight	1.8Kg incl PSU/2.8Kg incl PSU			
Dimensions	296w x 119h x 220d (mm)			
Operating Temp/Humidity	5°C to 40°C/0% to 90%			
Approval Certification	CE Approval			



360 Vision Technology Ltd

Unit 7 Seymour Court Manor Park Runcorn Cheshire WA7 1SY UK
 Tel:+44 (0)870 903 3601 Fax:+44 (0)870 903 3602
 info@360visiontechnology.com
 www.360visiontechnology.com

